

## DS-2CE16U1T-IT3F 4K Fixed Bullet Camera



- 8 MP bullet camera
- EXIR 2.0: advanced infrared technology with 60 m IR distance
- Water and dust resistant (IP67)
- 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)

## ▪ Specification

Camera	
Image Sensor	8.29 MP progressive scan CMOS
Max. Resolution	3840 (H) × 2160 (V)
Min. Illumination	0.01 Lux@(F2.0, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/12.5 s to 1/50,000 s;NTSC: 1/15 s to 1/50,000 s
Day & Night	IR Cut Filter
Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 180°, Rotation: 0 to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	2.8 mm, 3.6 mm, 6 mm, 8 mm, 12 mm fixed focal lens
Focal Length & FOV	102.2° (2.8 mm), 79° (3.6 mm), 50.8° (6 mm), 37.73° (8 mm), 23.96° (12 mm)
Lens Mount	M16
Illuminator	
Supplement Light Type	IR
Supplement Light Range	Up to 60 m
Smart Supplement Light	Yes
Image	
Image Settings	Brightness,Sharpness,AGC
Frame Rate	TVI: 8MP@12.5fps, 8MP@15fps, 4MP@25fps, 4MP@30fps, 2MP@25fps, 2MP@30fps CVI: 8MP@12.5fps, 8MP@15fps AHD: 8M@12.5fps, 8M@15fps CVBS: 960H P/N
Day/Night Mode	Auto/Color/BW (Black and White)
Wide Dynamic Range (WDR)	Digital WDR
Image Enhancement	BLC,HLC
Noise Reduction	2D DNR
White Balance	Auto/Manual
Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS,1 HD analog output
General	
Power	12 VDC ± 25%, max. 5.3 W *You are recommended to use one power adapter to supply the power for one camera.
Material	Front cover: Metal, Main body: Plastic
Dimension	81.9 mm × 86.7 mm × 217.9 mm (3.22" × 3.41" × 8.58" )
Weight	Approx. 435 g (0.96 lb.)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), humidity 90% or less (non-condensing)
Communication	HIKVISION-C
Language	English
Approval	
Protection	IP67

## ▪ Available Model

DS-2CE16U1T-IT3F

▪ **Accessory**

▪ **Optional**

**DS-1280ZJ-XS  
Junction Box**



**Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
www.hikvision.com



Follow us on social media to get the latest product and solution information.

