



## TECHNICAL

Input voltage	12/24Vdc
Current Absorption	22mA red 38mA blue 34mA green
Materials/colours	Polycarbonate
Dimensions	58X58X20mm
Connections	5 wirings 1m cable
Temperature	-10°C/+50°C
Grade protection	IP65
LED colours	RGB

KRO504RGBL is designed to be used as an indicator with high intensity RGB LED light. It is suitable for indoor or outdoor installations, flashing or steady mode selectable and 12Vdc or 24Vdc supply voltage. IP65 grade protection.

### Connections:

Yellow:	+Vdc positive common
Red:	-Vdc negative Red LED
Green:	-Vdc negative Green LED
Blue:	-Vdc negative blue LED
White:	-Vdc negative FLASHING

Supplying more LED together generates different colours. All LED supplied generated white colour.

Le caratteristiche riportate in questa nota tecnica sono di esclusiva proprietà di Vimo elettronica snc  
Le caratteristiche del prodotto possono variare in funzione delle condizioni ambientali.

Vimo Elettronica s.n.c di Cavalleri R. L. & C  
Via dell'Artigianato 32/Q 20865 Usmate Velate (MB)  
Tel: 039/672520, fax: 039/672568, e-mail: [info@vimo.it](mailto:info@vimo.it) [www.vimo.it](http://www.vimo.it)  
C.F.: 05096770150 P.IVA: 00804240968 C.C.I.A.A. DI MB REA MB-1176225

Revisione	01
del	01/16