


CODE: **AWO363** v1.2/IV  
 NAME: **LED/B-SIN**



## DESTINATION

### INTERLOGIX

KEYPADS: CS 5186 (LED), CS 5500 (LCD), ATS 1110 (LCD)

### SINTONY

KEYPADS: SAK 33, 34, 71, 72, 73, 74, 21

### CADDX NETWORK

KEYPADS: NX-1508E, NX-1516E(LED Slimline)

### GALAXY

KEYPADS: MK-7

### PARADOX

KEYPADS: SPC-1686V, ESP- 646

## TECHNICAL DATA

External dimensions of the enclosure:	W=169, H=190, D=50 [+/- 2mm]
External dimensions of the front panel:	W <sub>1</sub> =177, H <sub>1</sub> =195 [+/- 2mm]
Keyboard mounting dimensions:	W <sub>2</sub> =110, H <sub>2</sub> =185, D <sub>1</sub> =41 [+/- 2mm]
Weight net/gross:	0,85kg / 0,90kg [+/-0,1kg]
Operating environment:	class II, -10°C+ 40°C
Material description:	sheet steel DC01, thickness: 0,7mm, protection anticorrosion, color: RAL 9003
Destination:	indoor
Tamper protection:	1 x microswitch: opening, 0,5 A@50 V DC max. NC- contacts
Closing:	lockable (various code, two keys included)
Notes:	removable back mounting plate
Declaration, warranty:	RoHS, 2 year from the production date