



ZKTeco ZKBioSecurity 3.0 Access Control Devices List

V1.2 8/8/2017

No.	Device Type	Model Name	Firmware Version	Software Version
1	Controller	InBio160 Pro	AC Ver 5.7.7.3033 Jun 16 2017	ZKBioSecurity3.0.5.0_R or Above
		InBio260 Pro		
		InBio460 Pro		
2	Standalone Devices	inPulse	Ver8.0.1.3-4549-01 or Above	
		inPulse+	Ver8.0.1.3-4549-01 or Above	
		ProBio	Ver8.0.1.3-4549-01 or Above	
		ProCapture-T	Ver8.0.1.3-4549-01 or Above	
		ProRF-T	Ver8.0.1.3-4549-01 or Above	
		ProFAC	Ver8.0.1.3-4549-01 or Above	
		ProCapture-X	Ver 8.0.3.7-20170518 or Above	
ProCapture-WP	Ver 8.0.1.3- 4549 -01 or Above			



ZKTeco ZKBioSecurity 3.0 Elevator Control Devices List








V1.2 8/8/2017

No.	Devices	Model Name	Connection Mode	Firmware Version	Software Version	Remark
1	Elevator Controller	EC10	Online/Offline	Ver 7.0.0 Jul 01 2013 or Above	ZKBioSecurity3.0.5.0_R or Above	In the Offline mode, Elevator Control module can only support up to 31 Floors and personnel access level can only assigned in maximum 2 Elevators.
2	Elevator Floor Extension Board	EX16	Online/Offline			
3	Mifare Card Encoder	CR20WM	Offline			
4	RS485 Mifare Reader	KR100-RSEC				
5	Mifare Card	S50				



No.	Device Type	Model Name	Software Version	Remark
1	Hotel Lock	LH1000	ZKBioSecurity3.0.5.0_R or Above	
		LH2600		
		LH3000		
		LH3600		
		LH4000		
		LH5000		
2	Mifare Card Encoder	CR60W		
3	Mifare Card	S50/S70		Record Card must be S70 Mifare Card.

No.	Hardware	Usage	Accessories					Software Version
			Recommended					
			Brand	Model	USB Cable	Driver	Photo	
1	Card Priter	Print the information on the card for employees.	FARGO	DTC1250e	✓	Download from HID website		ZKBioSecurity 3.0.5.0_R or Above
2			IDP	SMART-50S	✓	Download from IDP website		

No.	Hardware	Usage	Accessories					Software Version	Remark
			Recommended						
			Brand	Model	USB Cable	Driver	Picture		
1	Fixed mount Barcode Scanner	Read barcodes that printed on the visitor's badge.	ZKTeco	ZKT-BS25/30	✓	NA		<p>ZKBioSecurity 3.0.5.0_R or Above</p> <p>Main Camera: 5 Mega pixels 2592*1944 Vice Camera: 2 Mega pixels 1600*1200 Scan size: Up to A3 Szie</p> <p>1.If customers need the camera stand, please noted that in the PO once its order. 2.There are possibilities that when using USB camera and High-speed portable HD Doc Scanner together, those devices will be interference.</p> <p>1.Create cost-effective paper labels for visitors. Offering ultra-fast, high-quality printing at up to 93 labels per minute, the QL-700 features an auto cutter, giving a clean and accurate finished edge and allowing for printing one or multiple labels at a time, eliminating wasted label sheets. 2.The "Plug & Label" feature supports quick label printing of most basic labels, with no software installation required.</p>	
2	Barcode Scanner (Hand Held)	Scan barcode on the visitor receipt or other certificates	MINDEO	MD2250+	✓	NA			
3	Card/Fingerprint Reader	Issue Card or Register fingerprint for visitors.	ZKTeco	CR10E&M/ ZK4500/ ZK8500R/ Live20R	✓	Embed in ZKBioSecurity			
4	High-speed Portable HD Doc Scanner	Take pictures of Certificate and signature etc.	ZKTeco	PDS3000	✓	Embed in ZKBioSecurity			
5	USB HD Network Camera	Take pictures of visitor's head portrait.	Logitech	C525	✓	NA			
6	Receipt Printer	Print common receipt for visitors.	ZKTeco	TP8016US	✓	Embed in ZKBioSecurity			
7	Sticker Printer	Print sticker receipt for visitors.	Brother	Brother QL-700	✓	Embed in ZKBioSecurity			

ZKTeco ZKBioSecurity 3.0 Video Linkage Devices List V1.2 8/8/2017

Brand	Hardware Type	Series	Model Name	Software Version	Functions					
					Capture (software linkage)	Video Storage		Video Preview	Maximum Connected Devices	Maximum Connected Cameras
ZKBioSecurity Server	NVR / DVR									
ZKTeco	IPC		GT-BB513	ZKBioSecurity3.0.5.0_R or Above	✓	✓	✗	✓	16	16
	IPC		GT-BD513		✓	✓	✗	✓	16	16
	IPC		GT-DC520-P		✓	✓	✗	✓	16	16
	IPC		PT-BA294K2		✓	✓	✗	✓	16	16
	IPC		PT-BA294K4		✓	✓	✗	✓	16	16
	IPC		PT-DA294K2		✓	✓	✗	✓	16	16
	NVR		GT-NR401		✗	✓	✓	✓	20	80
	NVR		ZKNV08025		✗	✓	✓	✓	20	160
	DVR		GT-ADR401M		✗	✓	✓	✓	20	80
	DVR/NVR		GT-ADR3208M		✗	✓	✓	✓	20	160
NVR	PT-NVR5104	✗	✓	✓	✓	20	80			
ZKTeco	IPC		ZKMD532		✓	✓	✗	✓	16	16
ZKTeco	IPC		ZKIP472		✓	✓	✗	✓	16	16
	IPC		ZKIR572		✓	✓	✗	✓	16	16
	NVR(4 channels)		ZK-NV0401		✗	✓	✓	✓	20	80
HIKVISION	IPC	DS	DS-2CD2012-I	ZKBioSecurity3.0.1.0 or Above	✓	✓	✗	✓	16	16
	NVR	DS	DS-7608NI-E2/8P		✓	✓	✓	✓	20	160
	Multi-DVR	DS	DS-7316HWI-5H		✓	✓	✓	✓	20	320
Dahua	IPC		DH-IPC-HFW4100S-V2	ZKBioSecurity3.0.1.0 or Above	✓	✓	✗	✓	16	16
			DH-HAC-HDW1100S		✓	✓	✗	✓	16	16
	NVR		NVR4104H-P		✓	✓	✓	✓	20	160
	DVR		DH/HCVR4104HS-V3		✓	✓	✓	✓	20	80
Dahua	HDCVI		HCVR5104H-S2	ZKBioSecurity3.0.1.0 or Above	✓	✓	✓	✓	20	80
	HDCVI		HCVR5104H-S3		✓	✓	✓	✓	20	80
	HDCVI		XVR5104		✓	✓	✓	✓	20	80
	HDCVI		HCVR5108H-S2		✓	✓	✓	✓	20	160
	HDCVI		HCVR5108H-S3		✓	✓	✓	✓	20	160
	HDCVI		XVR5108		✓	✓	✓	✓	20	160
	HDCVI		HCVR5116H-S2		✓	✓	✓	✓	20	320
	HDCVI		HCVR5116H-S3		✓	✓	✓	✓	20	320
	HDCVI		XVR5116		✓	✓	✓	✓	20	320
	HDCVI		HCVR5216A-S2		✓	✓	✓	✓	20	320
	HDCVI		HCVR5216A-S3		✓	✓	✓	✓	20	320
	HDCVI		HCVR7204A-S2		✓	✓	✓	✓	20	80
	HDCVI		HCVR4104HS-S2		✓	✓	✓	✓	20	80
	HDCVI		HCVR4104HS-S3		✓	✓	✓	✓	20	80
	HDCVI		XVR4104		✓	✓	✓	✓	20	80
	HDCVI		HCVR4108HS-S2		✓	✓	✓	✓	20	160
	HDCVI		HCVR4108HS-S3		✓	✓	✓	✓	20	160
	HDCVI		XVR4108		✓	✓	✓	✓	20	160
	HDCVI		HCVR4116HS-S2		✓	✓	✓	✓	20	320
	HDCVI		HCVR4116HS-S3		✓	✓	✓	✓	20	320
	HDCVI		XVR4116		✓	✓	✓	✓	20	320
	HDCVI		HCVR4208A-S2		✓	✓	✓	✓	20	160
	HDCVI		HCVR4216A-S2		✓	✓	✓	✓	20	320
	HDCVI		HCVR7104H-S3		✓	✓	✓	✓	20	80
	HDCVI		HCVR7108H-S3		✓	✓	✓	✓	20	160
HDCVI	XVR7104H-4M	✓	✓	✓	✓	20	80			
HDCVI	XVR5216AN	✓	✓	✓	✓	20	320			
Dahua	IPC		IPC-HDW4100SP	ZKBioSecurity3.0.1.0 or Above	✓	✓	✗	✓	16	16
	IPC		IPC-HDW4421MP		✓	✓	✗	✓	16	16
	IPC		IPC-HFW5202CP		✓	✓	✗	✓	16	16
	IPC		IPC-HFW-1220SP		✓	✓	✗	✓	16	16
	IPC		IPC-HF8301EP		✓	✓	✗	✓	16	16
	IPC		HFW4300EP		✓	✓	✗	✓	16	16
	IPC		HFW2100RP-VF		✓	✓	✗	✓	16	16
	IPC		HFW2320RP-ZS		✓	✓	✗	✓	16	16
	IPC		IPC-HDW1220SP		✓	✓	✗	✓	16	16
	IPC		IPC-HDBW5221EP-Z		✓	✓	✗	✓	16	16
	IPC		IPC-HF5221E		✓	✓	✗	✓	16	16
	IPC		IPC-HF5121E		✓	✓	✗	✓	16	16
	IPC		IPC-HFW5221E-Z		✓	✓	✗	✓	16	16
	IPC		IPC-HDBW5421E-Z		✓	✓	✗	✓	16	16
Dahua	NVR		NVR4204-4P	ZKBioSecurity3.0.1.0 or Above	✓	✓	✓	✓	20	80
	NVR		NVR4208-8P		✓	✓	✓	✓	20	160
	NVR		NVR4216-8P		✓	✓	✓	✓	20	320

ZKTeco ZKBioSecurity 3.0 3rd Party Onvif Cameras Supported List V1.08/8/2017

Brand	Hardware Type	Series	Model Name	Software Version	Functions					
					Capture (software linkage)	Video Storage		Video Preview	Maximum Connected Devices	Maximum Connected Cameras
ZKBioSecurity Server	NVR / DVR									
Axis	IPC		M3045-V	ZKBioSecurity3.0.5.0_R or Above	✓	✓	✗	✓	16	16
Panasonic	IPC		K-EW114L03AE		✓	✓	✗	✓	16	16
Geovision	IPC		GV-EFD1100		✓	✓	✗	✓	16	16
Sony	IPC		SNC-DH210T		✓	✓	✗	✓	16	16
	IPC		SNC-XM631		✓	✓	✗	✓	16	16

ZKTeco ZKBioSecurity 3.0 Photo & Video Capture Delay Detail

Functions	Status	Delay	Remark	Storage	Remark
Photo Capture on ZKBioSecurity Server (Software Linkage)	For Sale	2-5s	Only support capture on server.	ZKBioSecurity Server	Tips: 1. If users concerned about the real time of the photo and video records, ZKTeco do not recommend the Photo & Video Capture on ZKBioSecurity Server. 2. For the real time video capture function, please use the video record on NVR / DVR function instead.
Video Record on ZKBioSecurity Server	For Sale	3-8s	Only record video on server.	ZKBioSecurity Server	
Video Record on NVR / DVR	For Sale	2-5s (not include prerecord)	It has 10s prerecord time, so it can minimize the record delay scenario.	NVR / DVR	



No.	Application Scenarios	Server Quantity	Usage	Software Version	Recommended Database	Firewall	Server OS	Client's Browser	Screen Resolution	Minimum Server Configuration			Recommended Server										
										RAM	CPU	Hard Disk Space	Brand	Model Name	RAM	CPU	Hard Disk	Reference Budget					
1	SME Project	Single Server	Access Control: ≤50 devices (PUSH Firmware only)	ZKBioSecurity3.0.5.0_R or Above(*32bit Package)						4GB	Dual core processor with speeds of 2.4GHz or more	30GB	DELL	Optiplex 3020	8GB (4GB+4GB) 1600MHz DDR3	Intel Core i3-4130 CPU @3.4GHz quad core (i3/i5/i7)	500G	USD 560					
			Elevator Control: ≤10 devices																				
			Visitor: 1000 people per month																				
			Video Linkage Without NVR: ≤8 chls With NVR: 1-64 chls																				
			Patrol: ≤50 devices																				
			Hotel: ≤25 Locks																				
2	Medium Enterprise Project	Single Server	Access Control: ≤100 devices (PUSH Firmware only)	ZKBioSecurity3.0.5.0_R or Above(*32bit Package)	1. PostgreSQL(built-in) 2. SQL Server or Oracle (must installed by customer) 3. It's better to install the SQL Server or Oracle on remote server	TCP/UDP 8080 (Open Ports Required)	Windows 7 Windows 8 Windows 10 Windows Server 2008 Windows Server 2012	Chrome Opera Firefox IE11 Safari	1024*768 or more	8GB	Dual core processor with speeds of 2.4GHz or more	50GB	LENOVO	ThinkServer RD440	16GB ECC 1600MHz DDR3	Intel Xeon E5-2407 V2 @2.4GHz quad core	2*600GB SAS 3.5 inches ES hard disk 15K.	USD 2,900					
			Elevator Control: ≤ 30 devices																				
			Visitor: 2000 people per month																				
			Video Linkage Without NVR: ≤8 chls With NVR: 1-64 chls																				
			Patrol: ≤100 devices																				
			Hotel: ≤50 Locks																				
3	International Enterprise Project	Single Server	Access Control: ≤200 devices (PUSH Firmware only)	ZKBioSecurity3.0.5.0_R or Above(*32bit Package)	1. PostgreSQL(built-in) 2. SQL Server or Oracle (must installed by customer) 3. It's better to install the SQL Server or Oracle on remote server	TCP/UDP 8080 (Open Ports Required)	Windows 7 Windows 8 Windows 10 Windows Server 2008 Windows Server 2012	Chrome Opera Firefox IE11 Safari	1024*768 or more	8GB	Dual core processor with speeds of 2.4GHz or more	100GB	DELL	PowerEdgeR520	32GB DDR3	Intel Xeon E5-2407 V2 @2.4GHz quad core	DELL PERC S110 (1999G)	USD 3,000					
			Elevator Control: ≤ 50 devices																				
			Visitor: 5000 people per month																				
			Video Linkage Without NVR: ≤16 chls With NVR: 1-128 chls																				
			Patrol: ≤200 devices																				
			Hotel: ≤100 Locks																				
	Multiple Server	Access Control: >200 devices (PUSH Firmware only)	ZKBioSecurity3.0.5.0_R or Above(*32bit Package)												16GB	X64-capable dual core processor with speeds of 2.7GHz or more	200GB						
		Elevator Control: >50 devices																					
		Visitor: >20000 people per month																					
		Video Linkage Without NVR: ≤16 chls With NVR: 1-128 chls																					
		Patrol: > 200 devices																					
		Hotel: >100 Locks																					

*1. The 32bit package[EN_ZKBioSecurity3.0.5.0_R_X86] can be installed on both the 32bit and 64bit windows system.
 *2. This 64bit package[EN_ZKBioSecurity3.0.5.0_R_X64] can only be installed on 64bit windows system.

